

EXPLOSION-PROOF EXIT LIGHT



AXX-E



MODEL NO	: AXX-E
Certifications	
Global (IECEX)	
Gas	: Ex db eb mb q IIC T4/T5/T6 Gb
Dust	: Ex tb IIC 80°C / 95°C/130°C Db IP66
Rated voltage AC	: 100-277VAC or 100-347VAC
Rated voltage DC	: 12 V - 36 V
Rated frequency	: 50 / 60 Hz
Degree of protection	: IP66
Operation temperature	: -20°C~+60°C (T5 / T95°C) or -20°C~+40°C (T6 / T80°C)
Max surface temperature	: T6 for gas and T80°C for dust
Weight	: approx. 4.32 kg / 9.52 lb
Rated wattage	: Regular wattage in normal mode: 3W Max. wattage in normal mode: 10W
Lifespan	: 50,000 hours
Warranty	: 5 years
Batteries	: 3.7V, 2 A
Cable entry size	: M25×1.5, 3/4 NPT
Stopping plug	: M25×1.5
Emergency time	
Escape route sign luminaires	: 3 hours
Emergency lighting luminaires	: 3 hours
Charging time*	: ≥24 hours
Impact strength (IK code)	: IK08 (IEC 62262)
Installed terminal strip	: PE + N + L
Connection terminals solid max	: 4mm ²
Connection terminals finely stranded max	: 2.5mm ²

- Emergency control power supply specially designed for the luminaire. EMC/EMI function.
- 3-hour emergency operation. Central locking is available.
- Label content can be customized.
- Low working wattage for energy saving.
- Ingress protection rating IP66.
- Each lamp is equipped with a T-shaped unlocking tool that can be used for all lamps.
- DALI version available on request



Ordering Guide

Legend	Mounted Box
	AXXE/R/E
	AXXE/R/ER
	AXXE/R/EL
	AXXE/R/ED
	AXXE/R/M
	AXXE/R/MR
	AXXE/R/ML
	AXXE/R/MB
	AXXE/R/MT